

KEBUmat Wrapping devices

Product information

The **KEBUmat** wrapping device is a manual tool for the application of Kebutyl tape systems and the Kebulen-Tape B 80-C. The tapes are applied with ease in compliance with the required overlap and application tension. **KEBUmat** wrapping devices are built for extreme side conditions and a fast working pace. The different types of the **KEBUmat** wrapping device are perfectly suited for straight and bended pipes.



KEBUmat „Mini“

The **KEBUmat „Mini“** is specifically designed for the tape application at limited space conditions. It's suitable for pipes with a small nominal size (\geq DN 40 / 1,5").



KEBUmat „ST“

The **KEBUmat „ST“** is suitable for a variety of applications. It facilitates and accelerates the coating of straight pipes from DN 80 / 3" and pipe bends from DN 100 / 4".



KEBUmat „GR“

The **KEBUmat „GR“** allows the use of larger rolls for pipes up to DN 1400 / 56". The tapes have a maximum width of 150 mm and a roll diameter of 300 mm.

Typ	Material support [mm]	Tape width [mm]	Roll diameter [mm]	Nominal size		Minimal working height
				DN	Inch	
Mini	41	Max. 100	Max. 100	\geq 40	\geq 1,5"	20
ST	41	Max. 100	Max. 160	\geq 80 Pipe bends \geq DN 100	\geq 3"	30
GR	76 [3"]	Max. 150	Max. 300	\geq 300	\geq 12"	40

Additional accessories on demand, for example an extension arm and wrapping cage for KEBUmat "GR"

The information given in this publication is based on our knowledge and experience. The hints and instructions for use given therein have been compiled to the best of our knowledge on the basis of our tests and experience. Best results will be obtained if our products are used in a proper and expert way. Any protected rights and existing laws and regulations must be complied with the recipient. In all other respects our general terms and conditions shall apply.
-- Rev.: 00_11.04.2019 --